

FIX N GROUT

DESCRIPTION

Fix 'N' Grout is the perfect solution to tiling jobs around the house and is suitable for use with ceramic tiles on interior plaster, plasterboard, cement and concrete.



ADVANTAGES

- Dual purpose product for fixing & grouting.
- Dries bright white.

DIRECTION FOR USE

TILING

- Spread evenly onto the wall or surface to be tiled at the rate of approximately 1 square meter at a time to no more than 3mm in depth.
- Rib the adhesive using the combed edge of the applicator provided. Place tiles from the bottom working upwards, pressing tiles firmly into place with a slight twisting motion. Leave gaps of approximately 2mm around each tile.
- Wipe off any excess immediately, setting makes removal difficult. Allow to set for at least 4 hours before grouting.

GROUTING


- Apply straight from the tub using the straight edge of the applicator provided or use a dry cloth or sponge.
- Immediately, carefully remove excess grout from the face of the tiles with a cloth. Take particular care not to allow the product to dry on the face of tiles with gold leaf or other metallic or mirror finishes.
- Ensure joints are completely filled to avoid 'pinholing' as the grout dries.
- Coverage is up to 32 tiles of 15 x 15cm per 1kg tub.
- Replace plastic disc and lid immediately and securely. Protect from frost.

NOTE Fix 'N' Grout is formulated to withstand occasional immersion in water and is suitable for fixing and grouting in bathrooms and kitchens.

Tiles that come into direct contact with water must first be allowed to dry thoroughly (approximately 72 hours). Do not use for fixing tiles in swimming pools or for thick bed floor tiling.

AVAILABILITY

- 750g – TEF001
- 1.5kg – TEF002
- 3.75kg – TEF003
- 7.5lt – TEF005



FIX N GROUT

PRECAUTIONS

For more information and precautions for use refer to the safety data sheet.

NOTE

In case of doubt, we recommend you to contact our technical department, which will suggest the most appropriate adhesive for your purposes, or will conduct the test required to find it.

The technical information contained in this document, as well as our technical advice whether verbal or written, is the result of our experience with the product and should be considered as collaboration without compromise, since the use and / or final application of our adhesives is beyond our control, declining all liability for improper use. The customer is responsible to confirm and evaluate prior to use, by trial or test if the product conforms to required employment. The information, recommendations or advices contained herein are given in good faith, supplier makes no warranty or guarantee, express or implied, that the results described herein will be obtained under end-use conditions, or as to the effectiveness or safety of any design incorporating supplier's materials, products, services, recommendations or advice. Nothing in this or any other document shall alter, vary, supersede or operate as a waiver of any of the supplier's standard terms of sale.

So our guarantee is limited to ensure the quality of our products, according to our quality standards.



Arc Building Products
IDA Business & Technology Park,
Ballynattin, Arklow,
Co. Wicklow, Ireland.

www.arcbuildingproducts.ie

Phone: +353 (0)402 41200

Phone: +353 (0)402 32370

Fax: +353 (0)402 24168

Email: sales@arcbuildingproducts.ie